


...→ METRIC THREAD BRASS CABLE GLAND

→ PG THREAD BRASS CABLE GLAND

→ METRIK THREAD BRASS CABLE GLAND



→ <b>Material</b>	Brass, Nickel Plated
→ <b>Clamping Insert</b>	Polyamide 6
→ <b>Seal</b>	Thermoplastic Rubber
→ <b>Protection Class</b>	IP 68
→ <b>Temp. range</b>	- 40 C to + 100 C
→ <b>O-ring</b>	NBR

**METRIC THREAD BRASS CABLE GLAND**

AG Thread	Code	H mm.	GL mm.	mm.	Clamping Range
M12x1,5	OMBG-01	19	6	14	3-6,5
M16x1,5	OMBG-02	22	7	20	4-8
M20x1,5	OMBG-03	24	8	24	6-12
M25x1,5	OMBG-04	25	8	30	10-14
M32x1,5	OMBG-05	31	9	40	13-18
M40x1,5	OMBG-06	37	9	50	18-25
M50x1,5	OMBG-07	37	9	57	22-32
M63x1,5	OMBG-08	38	14	64-68	34-44

**METRIC LONG THREAD BRASS CABLE GLAND**

M12x1,5	OMBG-09	19	12	14	3-6,5
M16x1,5	OMBG-10	22	12	20	4-8
M20x1,5	OMBG-11	24	12	24	6-12
M25x1,5	OMBG-12	25	12	30	10-14
M32x1,5	OMBG-13	31	14	40	13-18
M40x1,5	OMBG-14	37	14	50	18-25
M50x1,5	OMBG-15	37	14	57	22-32
M63x1,5	OMBG-16	38	18	64-68	34-44