


...→ METRIC THREAD CONDUIT GLANDS

→ PG THREAD CONDUIT GLANDS

→ METRIK THREAD CONDUIT GLANDS



→ Material	Polyamide 6
→ Colour	RAL 7001 (Gray) RAL 7035 (L. Gray) RAL 9005 (Black)
→ Permanent operational temp.	- 40 C to + 100 C
→ Short term max. Operational temp.	+150 C

METRIC THREAD CONDUIT GLANDS

AG Thread	Gray Code	L. Gray Code	Black Code	A mm.	B mm.	GL mm.	D mm.	H mm.	L mm.	d mm.	d1 mm.
M12x1,5	MHG-01	MHL-01	MHB-01	7	16	8	17,5	29	20	13,3	11,6
M16x1,5	MHG-02	MHL-02	MHB-02	10	19	8	20	29	20	15,8	13,6
M16x1,5	MHG-03	MHL-03	MHB-03	11	22,5	8	24	32	23	20	17,7
M20x1,5	MHG-04	MHL-04	MHB-04	13	24,5	9	26	34	24	21,8	18,8
M20x1,5	MHG-05	MHL-05	MHB-05	15	26	10	27,5	35	24	23,5	20,7
M25x1,5	MHG-06	MHL-06	MHB-06	19	32	11	33,5	38	25,5	29,2	26,5
M32x1,5	MHG-07	MHL-07	MHB-07	24	41	11	42	43	30,5	38	34,7
M50x1,5	MHG-08	MHL-08	MHB-08	40,8	51,8	14	53,2	53,3	33,3	47,6	42,9
M63x1,5	MHG-09	MHL-09	MHB-09	53	61,6	14	64,6	57	37,2	57,9	53,7

SPECIAL METRIC THREAD CONDUIT GLANDS

M20x1,5	MHG-10	MHL-10	MHB-10	14,5	22,5	8	24	32	23	20	17,7
M25x1,5	MHG-11	MHL-11	MHB-11	17,5	26	10	27,5	35	24	23,5	20,7
M32x1,5	MHG-12	MHL-12	MHB-12	26,7	32	11	33,5	38	25,5	29,2	26,5
M40x1,5	MHG-13	MHL-13	MHB-13	31,5	41	11	42	43	30,5	38	34,7