


...→ METRIK THREAD CABLE GLANDS

→ PG THREAD CABLE GLANDS

→ METRIK THREAD CABLE GLANDS



→ Material	Polyamide 6
→ Colour	RAL 7001 (Gray) RAL 7035 (L. Gray) RAL 9005 (Black)
→ Protection Class	IP 68
→ Permanent operational temp.	- 40 C to + 100 C
→ Short term max. Operational temp.	+150 C
→ Seal	Thermoplastic Rubber

METRIK THREAD CABLE GLANDS

AG Thread	Gray Code	L. Gray Code	Black Code	H mm.	GL mm.	mm.	Clamping Range
M12x1,5	OMRG-01	OMRL-01	OMRB-01	23,9	8	15	3-6,5
M16x1,5	OMRG-02	OMRL-02	OMRB-02	27,7	8	19	4-8
M16x1,5	OMRG-03	OMRL-03	OMRB-03	29	10	22	5-10
M20x1,5	OMRG-04	OMRL-04	OMRB-04	29,2	10	24	6-12
M20x1,5	OMRG-05	OMRL-05	OMRB-05	32,8	10	27	10-14
M25x1,5	OMRG-06	OMRL-06	OMRB-06	37,9	10	33	13-18
M32x1,5	OMRG-07	OMRL-07	OMRB-07	40,7	10	42	18-25
M40x1,5	OMRG-08	OMRL-08	OMRB-08	51,3	10	53	22-32
M50x1,5	OMRG-09	OMRL-09	OMRB-09	53,5	18	60	30-38
M63x1,5	OMRG-10	OMRL-10	OMRB-10	55	18	65	34-44

METRÝK LONG THREAD CABLE GLANDS

M16x1,5	OMRG-11	OMRL-11	OMRB-11	29	15	22	5-10
M20x1,5	OMRG-12	OMRL-12	OMRB-12	29,2	15	24	6-12
M20x1,5	OMRG-13	OMRL-13	OMRB-13	32,8	15	27	10-14
M25x1,5	OMRG-14	OMRL-14	OMRB-14	37,9	15	33	13-18
M32x1,5	OMRG-15	OMRL-15	OMRB-15	40,7	18	42	18-25
M40x1,5	OMRG-16	OMRL-16	OMRB-16	51,3	18	53	22-32