


...→ PG THREAD CONDUIT GLANDS

→ PG THREAD CONDUIT GLANDS

→ METRIK THREAD CONDUIT GLANDS



- **Material** Polyamide 6
- **Colour** RAL 7001 (Gray)  
RAL 7035 (L. Gray)  
RAL 9005 (Black)
- **Permanent operational temp.** - 40 C to + 100 C
- **Short term max. Operational temp.** +150 C

**PG THREAD CONDUIT GLANDS**

AG Thread	Gray Code	L. Gray Code	Black Code	A mm.	B mm.	GL mm.	D mm.	H mm.	L mm.	d mm.	d1 mm.
PG 7	OHG-01	OHL-01	OHB-01	7	16	8	17,5	29	20	13,3	11,6
PG 9	OHG-02	OHL-02	OHB-02	10	19	8	20	29	20	15,8	13,6
PG 11	OHG-03	OHL-03	OHB-03	13,5	22,5	8	24	32	23	20	17,7
PG 13,5	OHG-04	OHL-04	OHB-04	15	24,5	9	26	34	24	21,8	18,8
PG 16	OHG-05	OHL-05	OHB-05	16	26	10	27,5	35	24	23,5	20,7
PG 21	OHG-06	OHL-06	OHB-06	19	32	11	33,5	38	25,5	29,2	26,5
PG 29	OHG-07	OHL-07	OHB-07	26	41	11	42	43	30,5	38	34,7
PG 36	OHG-08	OHL-08	OHB-08	40,8	51,8	14	53,2	53,3	33,3	47,6	42,9
PG 48	OHG-09	OHL-09	OHB-09	53	61,6	14	64,6	57	37,2	57,9	53,7