


...→ **PG THREAD FLAT TYPE CABLE GLANDS**

→ **PG THREAD FLAT TYPE CABLE GLANDS**

→ **METRIK THREAD FLAT TYPE CABLE GLANDS**



→ Material	Polyamide 6
→ Colour	RAL 7001 (Gray) RAL 7035 (L. Gray) RAL 9005 (Black)
→ Protection Class	IP 54
→ Permanent operational temp.	- 40 C to + 100 C
→ Short term max. Operational temp.	+150 C
→ Seal	Thermoplastic Rubber

PG THREAD FLAT TYPE CABLE GLANDS

AG Thread	Gray Code	L. Gray Code	Black Code	H mm.	GL mm.	mm.	Clamping Range
PG 7	ORG-11	ORL-11	ORB-11	21	8	15	3-5,6
PG 9	ORG-12	ORL-12	ORB-12	22	8	19	4,5-7
PG 11	ORG-13	ORL-13	ORB-13	22	8	22	6-9
PG 13,5	ORG-14	ORL-14	ORB-14	26	9	24	9-12
PG 16	ORG-15	ORL-15	ORB-15	28	10	27	11-14
PG 21	ORG-16	ORL-16	ORB-16	32	11	33	14-18
PG 29	ORG-17	ORL-17	ORB-17	35	11	42	18-25
PG 36	ORG-18	ORL-18	ORB-18	39	13	53	25-32