


...→ PG & METRIC BLIND STOPS



→ Material	Polyamide 6
→ Colour	RAL 7001 (Gray) RAL 7035 (L. Gray) RAL 9005 (Black)
→ Permanent operational temp.	- 40 C to + 100 C
→ Short term max. Operational temp.	+150 C

PG BLIND STOPS

AG Thread	Gray Code	L. Gray Code	Black Code	H mm.	GL mm.	D mm.
PG 7	OGK-01	OLK-01	OSK-01	8	6	15
PG 9	OGK-02	OLK-02	OSK-02	9	6	19
PG 11	OGK-03	OLK-03	OSK-03	9	6	22
PG 13,5	OGK-04	OLK-04	OSK-04	8,5	6	25
PG 16	OGK-05	OLK-05	OSK-05	8,5	6	27
PG 21	OGK-06	OLK-06	OSK-06	12	8	33
PG 29	OGK-07	OLK-07	OSK-07	12	8	44
PG 36	OGK-08	OLK-08	OSK-08	15	10	55

METRIC BLIND STOPS

M12x1,5	MOGK-01	MOLK-01	MOBK-01	8.5	6	15
M16x1,5	MOGK-02	MOLK-02	MOBK-02	10	7	20
M20x1,5	MOGK-03	MOLK-03	MOBK-03	10	7	24
M25x1,5	MOGK-04	MOLK-04	MOBK-04	14	10	30
M32x1,5	MOGK-05	MOLK-05	MOBK-05	14	10	37
M40x1,5	MOGK-06	MOLK-06	MOBK-06	15	10	46